



VENUS

VLTVL

Pancake Cylinders - Threaded Ram with Safety Lock Nut,
Single Acting , Spherical Saddle Without Gland Nut / Ram
Stopper (Type - Load Return)

Capacity 50-500T Stroke 45-50mm.
Max Operating Pressure 700kg/cm²



VLTVL Series V-Venus L-Single Acting Load Return T-Threaded ram VL-Very Low height

Capacity Ton	Capacity kN	Stroke mm	Model	Oil Capacity cm ³	Weight (Approx) kg	Closed Height mm	Cylinder OD mm	Bore Diameter mm	Ram Diameter mm	Saddle Diameter mm	Tilting Angle
50	550	50	VLTVL 50-50	393	15	125	140	100	100	90	5
100	1077	50	VLTVL 100-50	770	28.5	140	180	140	140	125	5
150	1589	45	VLTVL 150-45	1022	44	150	220	170	170	160	5
200	2199	45	VLTVL 200-45	1414	61	155	255	200	200	180	5
250	2661	45	VLTVL 250-45	1710	76	160	280	220	220	200	5
300	3167	45	VLTVL 300-45	2036	99	170	310	240	240	220	4
400	4008	45	VLTVL 400-45	2577	130	180	350	270	270	250	4
500	4948	45	VLTVL 500-45	3181	185	195	400	300	300	290	3